

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.



(19)

(11) Publication number: **59063668 A**

Generated Document.

PATENT ABSTRACTS OF JAPAN(21) Application number: **57173936**(51) Intl. Cl.: **H01M 6/36 H01M 10/39**(22) Application date: **05.10.82**

(30) Priority:

(43) Date of application
publication: **11.04.84**(84) Designated contracting
states:(71) Applicant: **ASAHI CHEM IND CO LTD**(72) Inventor: **SAOTOME ISAO
ARAKAWA TATSUMI
FUKUOKA MASAYUKI**

(74) Representative:

**(54) THERMAL
ACTIVATING BATTERY**


(57) Abstract:

PURPOSE: To provide a battery which outputs no power during storage and outputs power by heating by separating at least either one of a cathode active material, electrolyte, and an anode active material in a battery with a spacer such as paraffine.

CONSTITUTION: Nickel is used as a current collector 1, and paraffine having a melting point of 60~62°C is used as a spacer 4 which separates a negative active material 5 from electrolyte 3. Zinc plate is used as the negative active material 5. A positive mix 2 consists of acetylene black, manganese dioxide, and ammonium chloride. Electrolyte consists of ammonium chloride and zinc chloride mixed solution. Thickness of paraffine is 0.5mm or less. This battery outputs no current and voltage at room temperature. When the battery is placed in the air at 80°C for 30sec, it produces current and voltage and after 2 seconds, the battery outputs a power of 1.5V,

100mA/cm².

COPYRIGHT: (C)1984,JPO&Japio





[ABOUT DELPHION](#) [PRODUCTS](#) [NEWS/EVENTS](#) [MY ACCOUNT](#) [ID SEARCH](#) [HELP](#)
[Browse Codes](#) [IP Listings](#) [Prior Art](#) [Derwent](#) [Advanced](#) [Boolean](#) [Quick Number](#)

[Log Out](#) [Order Form](#) [Work Files](#) [View Cart](#)

The Delphion
Integrated
View

Other Views:
INPADOC

Title: **JP59063668A2: THERMAL ACTIVATING BATTERY**

► Want to see a more descriptive title highlighting what's new about this invention?

Country: **JP Japan**
Kind: **A**

Inventor(s): **SAOTOME ISAO**
ARAKAWA TATSUMI
FUKUOKA MASAYUKI

Applicant/Assignee:
ASAHI CHEM IND CO LTD
Inquire Regarding Licensing

News, Profiles, Stocks and More about this company

Issued/File Dates: **April 11, 1984 / Oct. 5, 1982**

Application Number: **JP1982000173936**

IPC Class: **H01M 6/36; H01M 10/39;**

Priority Number(s): **Oct. 5, 1982 JP1982000173936**

Abstract:

Purpose: To provide a battery which outputs no power during storage and outputs power by heating by separating at least either one of a cathode active material, electrolyte, and an anode active material in a battery with a spacer such as paraffine.

Constitution: Nickel is used as a current collector 1, and paraffine having a melting point of 60~62°C is used as a spacer 4 which separates a negative active material 5 from electrolyte 3. Zinc plate is used as the negative active material 5. A positive mix 2 consists of acetylene black, manganese dioxide, and ammonium chloride. Electrolyte consists of ammonium chloride and zinc chloride mixed solution. Thickness of paraffine is 0.5mm or less. This battery outputs no current and voltage at room temperature. When the battery is placed in the air at 80°C for 30sec, it produces current and voltage and after 2 seconds, the battery outputs a power of 1.5V, 100mA/cm².


COPYRIGHT: (C)1984,JPO&Japio

► See a clear and precise summary of the whole patent, in understandable terms.

Family: Show known family members

Other Abstract Info: none


Foreign References: No patents reference this one



[View Image](#)

1 page





[Nominate this
for the Gallery...](#)

[Subscribe](#) | [Privacy Policy](#) | [Terms & Conditions](#) | [FAQ](#) | [Site Map](#) | [Help](#) | [Contact Us](#)

© 1997 - 2002 Delphion Inc.